



## Technical Specifications

### V100E Electropneumatic Positioner

Input range:	4-20mA ( $R_i < 170$ ohms)	
Supply pressure:	22-145 PSI	0.15-1MPa
Linearity error:	<1.0% f.s.	
Hysteresis:	<0.5% f.s.	
Repeatability:	<0.5% f.s.	
Pressure Gain:	750 $P_{out}/P_{in}$	
Acc. To ISA S75.13	49% $P_{out}/P_{in}$	
Air Delivery:	SCFM	SLPM
@29 PSI (200kPa)	9.5	270
@87 PSI (600kPa)	28.3	800
@145 PSI (1Mpa)	47.1	1350
Air Consumption:	SCFM	SLPM
@29 PSI (200kPa)	0.18	5
@87 PSI (600kPa)	0.53	15
@145 PSI (1Mpa)	0.88	25
Temp Range:	-40° to 185° Fahrenheit -40° to 85° Celsius	
Air Connections:	1/4" NPT or G Threads	
Gauge port:	1/8" NPT or G Threads	
Cable entry:	1/2" NPT or M20x1.5 or PG 13.5	
Ingress & corrosion protection:	Nema 4X and IP 66	
Coating:	Powder Polyester Optional-Nickel	
Weight	3.8 lbs	1.7 kg