



Valve Accessories & Controls

Positioner	Spindle	Front Cover	Indicator	Cam
V200E-EX	D _____*	90 90 Degree 60 60 Degree 45 45 Degree 30 30 Degree 00 Blank	A Arrow B Raised	C _____*

*See spindle and cam selection below

Example: V200E-EX-D1-60-A-C3

Explosion proof, electropneumatic V200 positioner with namur spindle, 60 degree cover, arrow indicator, and 60 degree cam.

* Spindles

D1 Namur	D8 12 mm Dual Post
D2 1/2" Square	D9 Old Namur
D3 3/8" Square	D10 Namur-special-long
D4 Round (Linear)	D11 Octagon
D5 Double D	
D6 3/8" Square-long	
D7 3/4" Slotted	

* Cams

C1 90° & 180°, Linear + split range	C6 90° & 60°, Slot 0-100
C2 45° & 90°, Linear 0-100	C7 90°, Square root 0-100
C3 30° & 60°, Linear 0-100	C8 90°, Equal %
C4 60° & 120°, Linear 0-100	C9 70° Linear with 35° zero suppress
C5 90° & 60°, Pin 0-100	C10 90°, 4 way 25°, split range

Options:

High Gain Spool Valves	HG
Gas Approved I/P	GA

Gauges-must specify quantity and pressures.